

GluDown, Inc. Phone: (214) 504-2503 www.gludown.com sales@gludown.com

512 Purge & Cleaner

July 2025
GluDown, Inc.'s 512 Purge & Cleaner Adhesive is a high- performance, biodegradable solution designed for industrial use. Formulated from natural ingredients, it effectively removes adhesives while being safe for both users and the environment.
Delivered via a convenient aerosol system, it ensures precise, controlled application—whether used for purging adhesive canister hoses and guns or cleaning adhesive residues.
 As a purge, it enhances adhesive flow and spray pattern consistency, helping extend the life of hoses and spray guns. As a cleaner, it removes adhesive from a wide range of surfaces, including painted finishes, glass, porcelain, concrete, and most common substrates.
512 Purge & Cleaner is compatible with many plastics and vinyls, and any remaining residue can be easily rinsed away with water.
A
 Applications: Purge adhesive canister hose and guns
Adhesive remover
Product Color: Clear to Yellow
Biodegradable
Remove Residue with Water
Adapter fits standard adhesive canister hoses
2 to 4 uses when used as a hose and gun purge
Available in the following packaging types:
14 oz aerosol can (P/N: GD8212)
12 cans per case, 1,296 cans (108 cases) per pallet
 Product Color: Clear to Yellow Application Temperature: 40°F and rising to 100°F VOC Content:
VOC: 18.57%50 State compliant

Purge Application 1. Shake can well before use. 2. Turn off adhesive canister valve. 3. Point gun at dispensing container, pull gun trigger to release pressure. 4. Disconnect hose from canister, attach to cleaning adapter. 5. Thread can into adapter basket. 6. Ensure all fittings are secure and not leaking. 7. Point gun at dispensing container, pull trigger on gun. 8. Cleaner will flow through hose and gun pushing build up out the nozzle. Purge system for 30-60 seconds as needed. 9. Disassemble by unthreading can from basket. 10. Point gun at dispensing container, pull gun trigger to release pressure. 11. Disconnect hose from can, reattach to canister. 12. Turn canister valve on, test spray pattern. Repeat steps if necessary. **Adhesive Cleaner Application** Shake can well before use. 2. Use dispensing straw to spray 512 directly onto the surface. 3. Allow product to sit for at least a minute. 4. Wipe area with cloth. 5. If there is heavy buildup, use brush to help breakup adhesive. Repeat steps if necessary. Storage & Shelf Life Shelf Life: 12 months from manufacture date Rotate stock using oldest product first GLUDOWN, INC. MAKES NO WARRANTIES, EXPRESS Warranties OR IMPLIED, INCLUIDNG, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of any adhesive in a particular application. Given the variety of factors that can affect the use and performance of a GluDown, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose for the user's method of application. Limitation of remedies & If the GluDown, Inc. product is proved to be defective, THE liability EXCLUSIVE REMEDY, AT GLUDOWN, INC. OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE GLUDOWN, INC. PRODUCT. GluDown, Inc. shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including,

but not limited to, contract, negligence, warranty, or strict liability.