



GluDown, Inc.
Phone: (214) 504-2503
www.gludown.com
sales@gludown.com

GluDown® Foam Board Adhesive

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product Name: GluDown® Foam Board Adhesive

Revision Date: May 4, 2026

Version: 2.0

Part Numbers: GD1515

Manufactured For:

GluDown, Inc.
1501 10th Street, Suite 150
Plano, TX 75074
United States of America

Information Phone: 214-504-2503

Emergency Phone: Chemtrec 800-424-9300 / INTERNATIONAL 1-703-527-3887

Product/Recommended Uses: Adhesive

Restriction on Use: For commercial use only – not packaged or labeled for home use.

SECTION 2: HAZARDS IDENTIFICATION

Classification:

Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) -

Category 3

Aspiration Hazard – Category 1

Skin Irritation - Category 3

Eye Irritation - Category 2A

Aerosols - Category 1

Acute toxicity Dermal – Category 5

Acute toxicity Oral – Category 5

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms:



Signal Word:

Danger

Hazardous Statements - Physical:

H222 - Extremely flammable aerosol

H229 - Pressurized container: May burst if heated

Hazardous Statements - Health:

H336 - May cause drowsiness or dizziness

H304 - May be fatal if swallowed and enters airways

H316 - Causes mild skin irritation

H319 - Causes serious eye irritation

H313 - May be harmful in contact with skin

H303 - May be harmful if swallowed

Precautionary Statements - General:

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention:

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 - Use only outdoors or in a well-ventilated area

P251 - Pressurized container: Do not pierce or burn, even after use.

P233 - Keep container tightly closed.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

Precautionary Statements - Response:

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER/doctor if you feel unwell.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

Precautionary Statements - Storage:

P403 + P405 - Store in a well-ventilated place. Store locked up.

P405 - Store locked up.

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statements - Disposal:

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Acute toxicity of 12.8658% of the mixture is unknown

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENT

CAS	Chemical Name	% by Weight
0000115-10-6	METHYL ETHER	30% - 60%
0000109-66-0	PENTANE	15% - 40%
NA-ERAEnviro	Non Hazardous Solid	5% - 10%
NA-ERAEnviro	Non Hazardous Volatile	3% - 7%
0000067-64-1	ACETONE	1% - 5%
0000287-92-3	CYCLOPENTANE	0.50% - 1.5%
0000078-78-4	ISOPENTANE	0.50% - 1.5%
0064742-94-5	AROMATIC HYDROCARBON MIXTURE >C9	0.10% - 1%
0003710-84-7	DIETHYL HYDROXYLAMINE	0.02%
0000092-52-4	BIPHENYL	0.01%
0000091-20-3	NAPHTHALENE	0.01%
0064742-53-6	Petroleum Base Oil B	0.00%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4: FIRST-AID MEASURES

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

Inhalation:

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. Eliminate all ignition sources if safe to do so. Call a POISON CENTER/doctor if you feel unwell. Take precautions to ensure your own safety (e.g. wear appropriate protective equipment).

Skin Contact:

Rinse with lukewarm, gently flowing water for 5 minutes or until product is removed. Call a POISON CENTER/doctor if you feel unwell. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes or until medical aid is available. Store contaminated clothing under water and wash before re-use or discard. If skin irritation occurs or you feel unwell: Get

medical advice/attention. Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts).

Eye Contact:

If eye irritation persists: Get medical advice/attention. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face.

Ingestion:

Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Immediately call a POISON CENTER or doctor.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.
Large Fire : Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media:

Do not use straight stream of water.

Specific Hazards Arising from the Chemical:

Fire will produce irritating gases. Contents under pressure. May be ignited by friction, heat, sparks or flames. Containers can explode in a fire. Containers exposed to heat and flames may rupture with violent force. Cylinders exposed to fire may vent and release gas through pressure relief devices. Vapors will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to source of ignition and flash back.

Precautions for Firefighters:

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Equipment:

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE).

For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or

disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

SECTION 7: HANDLING AND STORAGE

General:

Wash hands after use. Avoid contact with skin, eye or clothing. Avoid breathing vapor or mist. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored. All containers must be properly labelled. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Ventilation Requirements:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements:

Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and strong oxidizers. Store in approved containers and protect against physical damage. Take precautionary measures against electrostatic discharge. To avoid fire or explosion, dissipate static electricity during transfer by ground and bonding containers and equipment before transferring material. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection:

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (ppm)	OSHA TWA (mg/m3)		OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)
ACETONE	A4	URT & eye irr; CNS impair	A4; BEI	1000	2400				1
AROMATIC HYDROCARBON MIXTURE >C9	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	500	2000				1
BIPHENYL		Pulm func		0.2	1				1
CYCLOPENTANE		CNS impair							
DIETHYL HYDROXYLAMINE		URT irr							
ISOPENTANE		Narcosis; resp tract irr							
NAPHTHALENE	A3	URT irr; cataracts; hemolytic anemia	Skin; A3; BEI	10	50				1
PENTANE		Narcosis; resp tract irr		1000	2950				1
Petroleum Base Oil B	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	500	2000				1

Chemical Name	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen	ACGIH TWA (ppm)
ACETONE			250	590				250
AROMATIC HYDROCARBON MIXTURE >C9								(L)[N159](L)[N800]
BIPHENYL			0.2	1				0.2
CYCLOPENTANE			600	1720				1000
DIETHYL HYDROXYLAMINE								2
ISOPENTANE								1000
NAPHTHALENE			10	50	15	75		10

PENTANE			120	350				1000
Petroleum Base Oil B								(L)[N159](L) [N800]

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
ACETONE		500	
AROMATIC HYDROCARBON MIXTURE >C9	[(L)[N159](L) [N800]]; [5 (I) [N159]5 (I) [N800]];		
BIPHENYL			
CYCLOPENTANE			
DIETHYL HYDROXYLAMINE			
ISOPENTANE			
NAPHTHALENE			
PENTANE			
Petroleum Base Oil B	[(L)[N159](L) [N800]]; [5 (I) [N159]5 (I) [N800]];		

A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, func - Function, impair - Impairment, irr - Irritation, pulm - Pulmonary, resp - respiratory, URT - Upper respiratory tract.

The information in this Section does not list non-hazardous components that might have relevant ACGIH TWA (mg/m3), ACGIH TWA (ppm), ACGIH Carcinogen, ACGIH TLV Basis, ACGIH Notations, OSHA TWA (ppm), OSHA TWA (mg/m3), OSHA Tables (Z1, Z2, Z3) regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	5.70565 lb/gal
Specific Gravity	0.68369
Density VOC	N/A lb/gal
VOC Actual	N/A g/l
% VOC	81.55580%
Appearance	Orange web spray
Odor Threshold	N.A.
Odor Description	Pungent solvent
pH	N.A.
Flammability	N.A.
Water Solubility	N.A.
Flash Point Symbol	N.A.
Flash Point	N.A.
Viscosity	N.A.
Lower Explosion Level	N.A.

Upper Explosion Level	N.A.
Vapor Pressure	N.A.
Vapor Density	N.A.
Freezing Point	N.A.
Melting Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Auto Ignition Temp	N.A.
Evaporation Rate	N.A.
Kinematic Viscosity	N.A.
Kinematic Viscosity Temperature	N.A.
VOC Composite Partial Pressure	N.A.

SECTION 10: STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability:

Stable under normal storage and handling conditions.

Conditions to Avoid:

Avoid heat, sparks, flame, high temperature, freezing and contact with incompatible materials.

Avoid all possible sources of ignition.

Possibility of Hazardous Reactions/Polymerization:

Will not occur.

Incompatible Materials:

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products:

Oxides of carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation:

Causes mild skin irritation.

0000067-64-1 ACETONE

Can cause skin irritation.

Serious Eye Damage/Irritation:

Causes serious eye irritation.

0000067-64-1 ACETONE

Exposure can irritate the eyes.

Respiratory/Skin Sensitization:

0000067-64-1 ACETONE

Can irritate the nose and throat causing coughing and wheezing.

Germ Cell Mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive Toxicity:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure:

May cause drowsiness or dizziness

0000067-64-1 ACETONE

May affect the kidneys and liver.

Specific Target Organ Toxicity - Repeated Exposure:

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Aspiration Hazard:

May be fatal if swallowed and enters airways

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

If liquid is swallowed, it may get into lungs by aspiration

Acute Toxicity:

May be harmful in contact with skin

May be harmful if swallowed

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is 4601.73 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is 4897.48 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

The Acute Toxicity Estimate (ATE) for an inhalation (dust and mist) exposure to this mixture is >5 mg/l

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

High concentration of vapors may cause intoxication

Chronic Exposure

Based on available data, the classification criteria are not met.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

0000067-64-1 ACETONE

Substance can be absorbed into the body by inhalation.

Potential Health Effects – Miscellaneous

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

0000091-20-3 NAPHTHALENE

Is an IARC, NTP or OSHA carcinogen. Tests in some laboratory animals demonstrate carcinogenic activity. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: kidneys, liver. Recurrent overexposure may result in liver and kidney injury. WARNING: This chemical is known to the State of California to cause cancer.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or

monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0000067-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m³ (4-hour exposure) (29)
 LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m³ (4-hour exposure) (29)
 LD50 (oral, female rat): 5800 mg/kg (24)
 LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)
 LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)
 LD50 (oral, mouse): 3000 mg/kg (32,unconfirmed)
 LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

0000091-20-3 NAPHTHALENE

LC50: Insufficient data LD50 (oral, mouse): 533 mg/kg (male); 710 mg/kg (female) (1)
 LD50 (oral, rat): 1780 mg/kg (2)

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

LC50 (Rodent - rat, Inhalation) : >590 mg/m³ (4 hour exposure) Toxic effects : Details of toxic effects not reported other than lethal dose value.
 LD50 (Rodent - rabbit, Administration onto the skin) : >2 mL/kg ,Toxic effects : Behavioral - somnolence (general depressed activity) Behavioral - changes in motor activity (specific assay) Behavioral - irritability

0064742-53-6 Petroleum Base Oil B

LC50 (Rodent - rat , Inhalation) : 2180 mg/m³ (4 hours exposure) Toxic effects : Lungs, Thorax, or Respiration - structural or functional change in trachea or bronchi.
 LD50 (Rodent - rat, Oral) : >5000 mg/kg, Toxic effects : Behavioral - somnolence (general depressed activity).
 LD50 (Rodent - rabbit, Administration onto the skin) : >2000 mg/kg, Toxic effects : Skin and Appendages - primary irritation (after topical exposure)

0000109-66-0 PENTANE

LC50 (rat): 117000 ppm (364000 mg/m³) (4-hour exposure) (12, unconfirmed)

0000078-78-4 ISOPENTANE

LC50 (mouse): 140,000 ppm (2-hour exposure).(3)

0000092-52-4 BIPHENYL

LD50 (oral, rat): 3280 mg/kg (7); 5040 mg/kg (8)

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Based on available data, the classification criteria are not met.

Persistence and Degradability:

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

Readily biodegradable.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Readily biodegradable

Bioaccumulative Potential:

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Has the potential to bioaccumulate.

Mobility in Soil:

0000067-64-1 ACETONE

The substance is not PBT / vPvB.

Other Adverse Effects:

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws. It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14: TRANSPORT INFORMATION

U.S. DOT Information:

Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)

UN/NA #: UN1950

Hazard Class: 2.1

Required Mark: Limited Quantity

IMDG Information:

Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)

UN/NA #: 1950

Hazard Class: 2.1

Required Placard: Limited Quantity

Marine Pollutant: No data available

IATA Information:

Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)

UN/NA #: UN1950

Hazard Class: 2.1

Required Mark: Limited Quantity

SECTION 15: REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0000115-10-6	METHYL ETHER	30% - 60%	DHS_COI - DHS_Chemical Of Interest, Canada_NPRI, DSL - Domestic Substance List, SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA), NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0000109-66-0	PENTANE	15% - 40%	DHS_COI - DHS_Chemical Of Interest, Canada_NPRI, DSL - Domestic Substance List, SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA), NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL)
NA-ERAEnviro	Non Hazardous Solid	5%-10%	SARA312
0000067-64-1	ACETONE	1.00% - 5%	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, VOC_exempt, TSCA - Toxic Substances Control Act (TSCA), NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0000078-78-4	ISOPENTANE	0.50% - 1.50%	DHS_COI - DHS_Chemical Of Interest, Canada_NPRI, DSL - Domestic Substance List, SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA), NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0000287-92-3	CYCLOPENTANE	0.50% - 1.50%	DSL - Domestic Substance List, SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA), NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0064742-94-5	AROMATIC HYDROCARBON MIXTURE >C9	0.10% - 1.00%	Canada_NPRI, DSL - Domestic Substance List, SARA312, VOC, IARCCarcinogen, TSCA - Toxic Substances Control Act (TSCA)
0003710-84-7	DIETHYL HYDROXYLAMINE	0.02% - 0.02%	DSL - Domestic Substance List, SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA)
0000091-20-3	NAPHTHALENE	0.01% - 0.01%	SARA313, Canada_NPRI, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, OC_HAPS, VOC, IARCCarcinogen, NTP_Carcinogen - National Toxicology Program Carcinogens, TSCA - Toxic Substances Control Act (TSCA), NEI - National Emissions Inventory, CA_Prop65, CA_Prop65_Type_Toxicity_Cancer, NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0000092-52-4	BIPHENYL	0.01% - 0.01%	SARA313, Canada_NPRI, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, OC_HAPS, VOC, TSCA - Toxic Substances Control Act (TSCA), NEI - National Emissions Inventory, NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0064742-53-6	Petroleum Base Oil B	0.00% - 0.00%	DSL - Domestic Substance List, SARA312, VOC, IARCCarcinogen, TSCA - Toxic Substances Control Act (TSCA), MA_RightToKnow - Massachusetts Right to Know

The information in this Section does not list non-hazardous components that might have relevant IARCCarcinogen, SARA312, TSCA - Toxic Substances Control Act (TSCA), VOC, DSL - Domestic Substance List regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.



WARNING: This product can expose you to chemicals including NAPHTHALENE, which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

SECTION 16: OTHER INFORMATION

GLOSSARY:

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.