

AEROSOL GUIDE



CONSTRUCTION ADHESIVE



FOAM BOARD ADHESIVE



EDU MIST ADHESIVE



CHALK LOCK COATING

Applications	Difficult bonding applications including Tilt-Up & Precast forming, vapor barrier, sound proofing, geotextiles	Bonding EPS and XPS insulation board, expansion joint foam, protection boards, block outs	Everyday jobsite use, repairs, abatement, HVAC insulation, surface protection	Temporary chalk line and markings preservation for framing, flooring, forming, and general applications
Bond Strength & Attributes	BEST High strength, durable bond, heat & water resistance	BETTER Aggressive, instant bond, pressure sensitive	GOOD Medium strength bond, low soak in	SPECIALTY Temporary chalk line retention, weather resistant
Spray Pattern & Color	Web spray White/Transparent	Web spray Orange	Mist spray White/Transparent	Mist spray Clear
Method of Use	Apply to both surfaces	Can be single side application; for higher strength, apply to both	Can be single side application; for higher strength, apply to both	Apply directly over chalk lines and markings
Yield per Can	55+ sq ft	45+ sq ft	100+ sq ft	Up to 800 linear feet
Ready Time	~1 minute	~1 minute	~1 minute	~1 minute
Time to Assemble	Up to 5 minutes	Up to 60 minutes	Up to 5 minutes	No assembly required
Shelf Life	18 months	18 months	18 months	18 months
Fill Weight	14 oz net	13 oz net	15 oz net	16 oz net
Signature Attribute	High strength, durable bond	Safe on EPS and XPS foam insulation board	Mist spray, medium weight bond	Preserves chalk lines and markings on active jobsites
Bonds to:				
Concrete	✓	✓	✓	✓
EPS / XPS Foam Board		✓		
Fabric	✓	✓	✓	
Foil	✓	✓	✓	
Metal	✓	✓	✓	✓
Paper	✓	✓	✓	✓
PE & PP Foam	✓	✓		
Plastic	✓	✓		
Wood	✓	✓	✓	✓

