

Chalk Lock[®] Cleaner

Technical Data Sheet Date

September 2026

Product Description

GluDown, Inc.'s Chalk Lock[®] Cleaner is designed to aid in the removal of Chalk Lock[®] coating from hard smooth surfaces. Its solvent technology and blast spray pattern attacks the Chalk Lock[®] coating, helping to release it from the coated surface. Chalk Lock[®] Cleaner can also be used to remove heavy duty chalk lines and other markings. Its fast evaporation action leaves the surface clean with no cleaning agent residue.

Features

- Aids in the removal of Chalk Lock[®] coating from hard smooth surfaces
- Can be used for removing heavy duty chalk lines and other markings
- Fast evaporation
- No cleaning agent residue
- 50 State VOC Compliant

Packaging

- 15 oz (426 g) net weight aerosol can
- Part Number: GD8311
- 12 cans per case, 1296 cans (108 cases) per pallet

Technical Properties

- Product type: Solvent Aerosol Cleaner
- Can spray orientation: 90 Degree
- Application temperature: 40°F and rising to 100°F
- Recommended spray distance: 8 to 10 inches (20 to 25 cm)
- VOC category and limit: General Purpose Cleaner 8%, 50 state compliant
- For industrial and professional use

General Application

1. Shake can well before use.
2. Face valve to surface.
3. Spray onto Chalk Lock[®] coating. Recommended spray distance: 8 to 10 inches (20 to 25 cm).
4. Move the can continuously during application to prevent buildup on the substrate.
5. Allow to dwell for approximately 15 seconds.
6. Rub area with cloth or sponge to mechanically remove coating or markings.
7. Rotate or replace cloth or sponge as removed coating builds up.
8. Repeat steps as necessary to remove coating.

Chalk Lock® Cleaner

Safety & Handling

- DANGER: Extremely flammable aerosol. Pressurized container may burst if heated.
- Use only outdoors or in a well-ventilated area. Avoid breathing vapors or spray.
- Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
- Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
- Wear protective gloves, protective clothing, and eye/face protection.
- Keep out of reach of children. Read the product label and current Safety Data Sheet before use.

Storage & Shelf Life

- Store in a well-ventilated place with the container tightly closed.
- Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C).
- Shelf life: 18 months from manufacture date.

Disposal

Dispose of contents and container through an appropriate disposal or recycling center in full compliance with federal, state, and local laws. The user is responsible for determining whether the product meets applicable hazardous-waste criteria at the time of disposal.

Warranties

GLUDOWN, INC. MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application. Many factors can affect product use and performance. Because some factors are uniquely within the user's knowledge and control, the user must evaluate the product for the intended purpose and application method.

Limitation of Remedies & Liability

If the GluDown, Inc. product is proved to be defective, THE EXCLUSIVE REMEDY, AT GLUDOWN, INC. OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE GLUDOWN, INC. PRODUCT. GluDown, Inc. shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including contract, negligence, warranty, or strict liability.

Refer to the current product label and Safety Data Sheet for complete precautions, first-aid information, and regulatory details.